ARISE

NET-80-II



Product specification

INTERIOR TRACK LIGHT				
Cut out	-	_		
Dimension	D=Ø80 x H= 141mm	· 000 : E		
		• 205		
		0 0 .		
		• 100 •		

Technical description				
Article number	1519.206			
LED Consumption	25.5W			
Current	700mA			
сст	2700K	3000K	4000K	
Lumen *1	2565lm	2670lm	2712lm	
Øsystem ^{*3}	-	-	-	
Voltage	36.5V			
Reflector	12°/24°/40°			
CRI	90+			
Driver	Remoted, I/F	P: 90-264V 50/60	HZ	
	O/P: 15-50	V 700mA 35w Ma	ıx	

Photometric

Technical character		
Insulation	CLASS I	
Protection	IP 20	
Tilt	0~90°	
Rotate	±65°	
Operating temperature	-20~40 °C	
Average Failure Time	L70(10k) >60000 (h)	

Materials		
Luminaire	extruded aluminum body	
Lummane	-	
Reflector	plastic-PC	
Heat sink	forged aluminum	
Color available	black	

Package

inner box - mm 1 kg

outer box - mm 0 kg / 0 in 1

Accessories

None

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX): this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

