


LIBRA

Product specification

**INTERIOR RECESSED DOWN LIGHT**

Installation	Ceiling recessed
Cut out	Ø82mm
Dimension	D=Ø94 x H= 69mm

**Technical description**

Article number	1518.119		
LED Consumption	17.5W		
Current	500mA		
CCT	2700K	3000K	4000K
Lumen *1	1916lm	1994lm	2388lm
Øsystem*3	-	-	-
Voltage	35V		
Reflector	12°/24°/40°		
CRI	90+		
Driver	Remoted, I/P : 100-240V 50/60HZ O/P : 500mA		

Technical character

Insulation	CLASS III
Protection	IP65
Tilt	-
Rotate	-
Operating temperature	-20~40 °C
Average Failure Time	L70(10k) >60000 (h)

Materials

Luminaire	aluminum die cast
Reflector	plastic-PC
Heat sink	aluminum die cast
Color available(Bezel)	white / black
Color available(Baffle)	black / white / gold / blue

Package

inner box	mm 1 kg
outer box	mm 0 kg / 0 in 1

Photometric**Accessories**

None

Remarks

*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

B

I