


SUNTEC



Product specification

INTERIOR RECESSED DOWN LIGHT

Installation	Ceiling recessed
Cut out	□=90 x 90mm
Dimension	D=□95 x H= 100mm



Technical description

Article number	1618.111		
LED Consumption	12.8W		
Current	350mA		
CCT	2700K	3000K	4000K
Lumen ^{*1}	1336lm	1387lm	1411lm
Øsystem^{*3}	-	-	-
Voltage	36.5V		
Reflector	20°/30°		
CRI	90+		
Driver	Remoted, I/P : 90-264V 50/60HZ O/P : 15-50V350mA 35w Max		

Technical character

Insulation	CLASS III
Protection	IP 44
Tilt	-
Rotate	-
Operating temperature	-20~40 °C
Average Failure Time	L70(10k) >60000 (h)

Materials

Luminaire	steel bezel and housing
Reflector	anodized aluminum
Heat sink	aluminum die cast
Bezel color available	white/black
Baffle color available	white/black

Package

inner box	mm 1 kg
outer box	mm 0 kg / 0 in 1

Photometric

Accessories

None

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

