ARISE

NOTOR-108



Product specification

| INTERIOR RECESSED DOWN LIGHT | | | | |
|------------------------------|------------------|----------|--|--|
| nstallation | Ceiling recessed | | | |
| ut out | Ø100mm | | | |
| imension | D=Ø108 x H=84mm | 560 | | |
| | | • Ø108 • | | |
| | | | | |
| | | | | |

| Technical description | | | | |
|-----------------------|--------------|----------------------------------|--------|--|
| Article number | 1518.301 | | | |
| LED Consumption | 12.8W | | | |
| Current | 350mA | | | |
| ССТ | 2700K | 3000K | 4000K | |
| Lumen *1 | 1336lm | 1387lm | 1411lm | |
| Øsystem ^{*3} | - | - | - | |
| Voltage | 36.5V | | | |
| Reflector | 20°/40° | | | |
| CRI | 90+ | | | |
| Driver | Remoted, I/I | P: 90-264V 50/60 |)HZ | |
| | O/P: 12~4 | O/P: 12~48 Vdc/350mA,16Watt max. | | |

Photometric

| Technical character | | |
|-----------------------|---------------------|--|
| Insulation | CLASS III | |
| Protection | IP 20 | |
| Tilt | 0~90° | |
| Rotate | 0~355° | |
| Operating temperature | -20~40 °C | |
| Average Failure Time | L70(10k) >60000 (h) | |

| Materials | | | |
|-----------------|-------------------|--|--|
| Luminaire | aluminum die cast | | |
| Reflector | plastic-PC | | |
| Heat sink | forged aluminum | | |
| Color available | white / black | | |
| | | | |
| | | | |

Package

 inner box
 mm 1 kg

 outer box
 mm 0 kg / 0 in 1

Accessories

None

Remarks



- *1. LUMEN : for LED chip test result based on Tc=85°C.
 - This is the ideal (Maximum) lumen. This lumen information is from the LED supplier
- *3. LUMEN(Øsystem) (Total FLUX): this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.