ARISE

NOTOR-Projector



Product specification

INTERIOR RECESSED DOWN LIGHT			
nstallation	Ceiling recessed	•	
Cut out	Ø62mm	5 W B	
Dimension	D=Ø69 x H= 68mm	. ø30 • ø69	

Technical description		
Article number	1468.102	
LED Consumption	3W	
Current	700mA	
сст	2864-3228K	
Lumen *1	115lm	
Øsystem ^{*3}		
Voltage	3Vdc	
Reflector	15°	
CRI	80+	
Driver	Remoted, I/P:100V-240V,50-60/HZ,	
	O/P:700mA	

Photometric

Technical character		
Insulation	CLASS III	
Protection	IP 20	
Tilt	0~55°	
Rotate	0~355°	
Operating temperature	-20~40 °C	
Average Failure Time	L70(6k) >36000 (h)	

Materials		
Luminaire	aluminum die cast	
Reflector	Optic lens	
Heat sink	aluminum die cast	
Color available	white / black	

Package

 inner box
 mm 1 kg

 outer box
 mm 0 kg / 0 in 1

Accessories

None

Remarks



- *1. LUMEN: for LED chip test result based on Tc=85°C.
 - This is the ideal (Maximum) lumen. This lumen information is from the LED supplier
- *3. LUMEN(Øsystem) (Total FLUX): this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.