


## NOTOR-69



## Product specification

**INTERIOR RECESSED DOWN LIGHT**

<b>Installation</b>	Ceiling recessed
<b>Cut out</b>	Ø64mm
<b>Dimension</b>	D=Ø69 x H= 68mm

**Technical description**

<b>Article number</b>	1568.100.
<b>LED Consumption</b>	3W
<b>Current</b>	700mA
<b>CCT</b>	2864-3228K
<b>Lumen <sup>*1</sup></b>	115lm
<b>Øsystem<sup>*3</sup></b>	- - -
<b>Voltage</b>	3Vdc
<b>Reflector</b>	15°
<b>CRI</b>	80+
<b>Driver</b>	Remoted, I/P:100V-240V,50-60/HZ, O/P:700mA

**Technical character**

<b>Insulation</b>	CLASS III
<b>Protection</b>	IP 20
<b>Tilt</b>	0~10°
<b>Rotate</b>	0~355°
<b>Operating temperature</b>	-20~40 °C
<b>Average Failure Time</b>	L70(6k) >36000 (h)

**Materials**

<b>Luminaire</b>	aluminum die cast
<b>Reflector</b>	Optic lens
<b>Heat sink</b>	aluminum die cast
<b>Color available</b>	white / black

**Package**

inner box	mm 1 kg
outer box	mm 0 kg / 0 in 1

**Photometric****Accessories**

None

**Remarks**

\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.