




AGILE-119-F

**Product specification**



| <b>INTERIOR RECESSED DOWN LIGHT</b> |                  |
|-------------------------------------|------------------|
| <b>Installation</b>                 | Ceiling recessed |
| <b>Cut out</b>                      | Ø122             |
| <b>Dimension</b>                    | D=Ø160 H=225     |



**Technical description**

|                              |  |        |        |
|------------------------------|--|--------|--------|
| <b>Article number</b>        | 1518.202   |        |        |
| <b>LED Consumption</b>       | 25.5W  |        |        |
| <b>Current</b>               | 700mA  |        |        |
| <b>CCT</b>                   | 2700K  | 3000K  | 4000K  |
| <b>Lumen <sup>*1</sup></b>   | 2565lm   | 2670lm | 2712lm |
| <b>Øsystem <sup>*3</sup></b> | -  | -      | -      |
| <b>Voltage</b>               | 36.5V  |        |        |
| <b>Reflector</b>             | 20°/40°  |        |        |
| <b>CRI</b>                   | 90+  |        |        |
| <b>Driver</b>                | Remoted, I/P : 90-264V 50/60HZ<br>O/P : 15-50V 700mA 35w Max |        |        |

**Technical character**

|                              |                     |
|------------------------------|---------------------|
| <b>Insulation</b>            | CLASS II            |
| <b>Protection</b>            | IP 20               |
| <b>Tilt</b>                  | -                   |
| <b>Rotate</b>                | -                   |
| <b>Operating temperature</b> | -20~40°C            |
| <b>Average Failure Time</b>  | L70(10k) >60000 (h) |

**Materials**

|                                  |                   |
|----------------------------------|-------------------|
| <b>Luminaire</b>                 | steel             |
| <b>Trimless recessed frame</b>   | steel             |
| <b>Reflector(inner)</b>          | anodized aluminum |
| <b>Reflector(outer)</b>          | plastic-PC        |
| <b>Heat sink</b>                 | forged aluminum   |
| <b>Reflector color available</b> | silver / white    |

**Package**

|                  |   |    |               |
|------------------|---|----|---------------|
| <b>inner box</b> | - | mm | 1 kg          |
| <b>outer box</b> | - | mm | 0 kg / 0 in 1 |

**Photometric**

**Accessories**

None

**Remarks**



\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.