

## CHANNEL-S2




## Product specification

## INTERIOR RECESSED DOWN LIGHT

Installation Track light

Cut out

Dimension



## Technical description

Article number	1617.403B	1617.403B-V
LED Consumption	12.8WX2	12.8WX2
Current	-	-
CCT	3000K	3000K
Lumen *1	1387 (lm)X2	1387 (lm)X2
Øsystem*3	-	-
Voltage	100-240V AC	100-240V AC
Reflector	10°/15°/30°	10°/15°/30°
CRI	90+	90+
Driver		

## Technical character

Insulation	CLASS I
Protection	IP 20
Tilt	-
Rotate	-
Operating temperature	-20~40 °C
Average Failure Time	L70(6k) >36000 (h)

## Materials

Luminaire	aluminum extruded
Reflector	lens
Heat sink	aluminum extruded
Color available	white / black

## Package

inner box	mm 1 kg
outer box	mm 0 kg / 0 in 1

## Photometric

## Accessories

None

## Remarks



\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.