


## HADES



## Product specification

**INTERIOR COMBO LIGHT**

|              |                   |
|--------------|-------------------|
| Installation | Ceiling recessed  |
| Cut out      | □166mm            |
| Dimension    | D=□159 x H= 125mm |

**Technical description**

|                 |  |        |        |
|-----------------|--|--------|--------|
| Article number  | 1514.427-1   |        |        |
| LED Consumption | 25.9W  |        |        |
| Current         | 700mA  |        |        |
| CCT             | 2700K  | 3000K  | 4000K  |
| Lumen *1        | 2447lm   | 2559lm | 2636lm |
| Øsystem*3       | -  | -      | -      |
| Voltage         | 37.1V  |        |        |
| Reflector       | 12°/24°/40°  |        |        |
| CRI             | 90+  |        |        |
| Driver          | Remoted, I/P : 90-264V 50/60HZ<br>O/P : 15-50V 700mA 35w Max |        |        |

**Technical character**

|                       |                     |
|-----------------------|---------------------|
| Insulation            | CLASS III           |
| Protection            | IP 20               |
| Tilt                  | 0~30°               |
| Rotate                | -                   |
| Operating temperature | -20~40 °C           |
| Average Failure Time  | L70(10k) >60000 (h) |

**Materials**

|                         |                                    |
|-------------------------|------------------------------------|
| Luminaire               | aluminum die cast<br>steel housing |
| Trimless recessed frame | steel                              |
| Reflector               | plastic-PC                         |
| Heat sink               | forged aluminum                    |
| Color available         | white / black                      |

**Package**

|           |                  |
|-----------|------------------|
| inner box | mm 1 kg          |
| outer box | mm 0 kg / 0 in 1 |

**Photometric****Accessories**

\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

