


## HADES



## Product specification

**INTERIOR COMBO LIGHT**

Installation	Ceiling recessed
Cut out	□175mm
Dimension	D=□188 x H= 129mm

**Technical description**

Article number	1414.418-1		
LED Consumption	25.9W		
Current	700mA		
CCT	2700K	3000K	4000K
Lumen *1	2447lm	2559lm	2636lm
Øsystem*3	-	-	-
Voltage	37.1V		
Reflector	15°/40°		
CRI	90+		
Driver	Remoted, I/P : 90-264V 50/60HZ O/P : 15-50V 700mA 35w Max		

**Technical character**

Insulation	CLASS III
Protection	IP 20
Tilt	0~30°
Rotate	-
Operating temperature	-20~40 °C
Average Failure Time	L70(10k) >60000 (h)

**Materials**

Luminaire	aluminum die cast steel housing
Reflector	anodized aluminum
Heat sink	forged aluminum
Color available	white / black

**Package**

inner box	mm 1 kg
outer box	mm 0 kg / 0 in 1

**Photometric****Accessories**S8-1  
reflector+snootH8-1  
reflector+  
honeycomb louverSG8-1  
reflector+  
striped glass

\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture,  
this is the real lumen with the loss because of different design of reflectors and fixtures.

