


AMIGO-SW-TLB1

Product specification

**INTERIOR RECESSED DOWN LIGHT**

| | |
|--------------|-------------------|
| Installation | Ceiling recessed |
| Cut out | □154mm |
| Dimension | D=□145 x H= 152mm |

**Technical description**

| | | | |
|-----------------|--|--------|--------|
| Article number | 1514.404-1 | | |
| LED Consumption | 25.5W | | |
| Current | 700mA | | |
| CCT | 2700K | 3000K | 4000K |
| Lumen *1 | 2565lm | 2670lm | 2712lm |
| Øsystem*3 | - | - | - |
| Voltage | 36.5V | | |
| Reflector | 20°/40° | | |
| CRI | 90+ | | |
| Driver | Remoted, I/P : 90-264V 50/60HZ O/P : 15-50V 700mA 35w Max | | |

Technical character

| | |
|-----------------------|---------------------|
| Insulation | CLASS III |
| Protection | IP 20 |
| Tilt | 0~30° |
| Rotate | - |
| Operating temperature | -20~40 °C |
| Average Failure Time | L70(10k) >60000 (h) |

Materials

| | |
|-----------------|------------------------------------|
| Luminaire | aluminum die cast steel housing |
| Reflector | anodized aluminum |
| Heat sink | forged aluminum |
| Color available | white / black |

Package

| | |
|-----------|------------------|
| inner box | mm 1 kg |
| outer box | mm 0 kg / 0 in 1 |

Photometric**Accessories**

None

Remarks

*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

