


POLE-L-S



Product specification

INTERIOR LED LINEAR LIGHT	
Installation	System light
Cut out	
Dimension	17.5 X26x Lmm
	L=100mm
	L=300mm
	L=600mm



1710.004A : 100mm
1710.004B : 300mm
1710.004C : 600mm

Technical description

Article number	1710.004A-V	1710.004B-V	1710.004C-V
LED Consumption	2W	6W	12W
Current	-	-	-
CCT	3000K	3000K	3000K
Lumen ^{*1}	-	-	-
Øsystem^{*3}	128 (lm)	372 (lm)	737 (lm)
Voltage	24V DC		
Reflector	120°		
CRI	80+		
Driver			

Technical character

Insulation	CLASS III
Protection	IP 20
Tilt	-
Rotate	-
Operating temperature	-20~40 °C
Average Failure Time	L70(6k) >36000 (h)

Materials

Luminaire	aluminum extruded body and plastic end cap PC diffuser
Reflector	
Heat sink	aluminum extruded
Color available	black

Package

inner box	mm 1 kg
outer box	mm 0 kg / 0 in 1

Accessories

None

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

Photometric

