

## POLE-S




## Product specification

## INTERIOR TRACK LIGHT

**Installation** System light

**Cut out**

**Dimension**



## Technical description

<b>Article number</b>	1719.203-V
<b>LED Consumption</b>	2.2W
<b>Current</b>	-
<b>CCT</b>	3000K
<b>Lumen <sup>*1</sup></b>	-
<b>Øsystem<sup>*3</sup></b>	50~70 (lm)
<b>Voltage</b>	24V DC
<b>Reflector</b>	8°-20°
<b>CRI</b>	80+

**Driver**

## Technical character

<b>Insulation</b>	CLASS III
<b>Protection</b>	IP 20
<b>Tilt</b>	0~45°
<b>Rotate</b>	0~360°
<b>Operating temperature</b>	-20~40 °C
<b>Average Failure Time</b>	L70(6k) >36000 (h)


## Materials

<b>Luminaire</b>	aluminum body and plastic base
<b>Reflector</b>	PMMA Lens
<b>Heat sink</b>	aluminum
<b>Color available</b>	white / black

## Package

<b>inner box</b>	mm 1 kg
<b>outer box</b>	mm 0 kg / 0 in 1

## Photometric



## Accessories

None

## Remarks



\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.