Hammenullis

POLE-K




Product specification

INTERIOR TRACK LIGHT Installation System light

Installation Cut out

Dimension



Technical description		
Article number	1917.400-5-V	
LED Consumption	11W	
Current	-	
сст	3000K	
Lumen ^{*1}	1000 (lm)	
Øsystem ^{*3}	-	
Voltage	24V DC	
Reflector	15°/30°/40°	
CRI	90+	
Driver		

Technical character		
Insulation	CLASS III	
Protection	IP 20	
Tilt	0~180°	
Rotate	-	
Operating temperature	-20~40 °C	
Average Failure Time	L70(6k) >36000 (h)	

Materials		
Luminaire	aluminum extruded body and plastic end cap	
Reflector	PMMA Lens	
Heat sink	aluminum extruded	
Color available	white / black	

Package

inner box outer box mm 1 kg mm 0 kg / 0 in 1

Accessories

None

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

Photometric

