

SLIMDUET-W2



Product specification

INTERIOR SYSTEM LIGHT	
Installation	system light
Cut out	-
Dimension	64x33mm L:143mm

Technical description	
Article number	1817.407A-V
LED Consumption	11W
Current	-
CCT	3000K
Lumen ^{*1}	462lm
Øsystem^{*3}	-
Voltage	24vdc
Reflector	wallwash
CRI	90+
Driver	-

Technical character	
Insulation	CLASS I
Protection	IP 20
Tilt	-
Rotate	-
Operating temperature	-20~40 °C
Average Failure Time	L70(6k) >36000 (h)

Materials	
Luminaire	aluminum extruded PC
Reflector	-
Heat sink	-
Color available	white / black

Package

inner box	mm 1 kg
outer box	mm 0 kg / 0 in 1

Accessories

None

Remarks




*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

Photometric



h (m)	D (m)	E (lx)
82°		
1.0	1.45	256
2.0	2.90	64
3.0	4.35	28
4.0	5.80	16
5.0	7.25	10