


KANO

Product specification



INTERIOR COMBO LIGHT

| | |
|---------------------|------------------|
| Installation | Ceiling recessed |
| Cut out | 67x69mm |
| Dimension | 77x77x H=61mm |



| Technical description | |
|------------------------|--|
| Article number | 1814.413 |
| LED Consumption | 2.2W x4 |
| Current | 700mA |
| CCT | 3000K |
| Lumen *1 | 200lm x4 |
| Øsystem*3 | - |
| Voltage | - |
| Reflector | 15°/30°/40° |
| CRI | 90+ |
| Driver | Remoted, I/P : 90-264V 50/60HZ O/P : 9-24V 700mA Max16w |

| Technical character | |
|------------------------------|--------------------|
| Insulation | CLASS I |
| Protection | IP 20 |
| Tilt | - |
| Rotate | - |
| Operating temperature | -20~40 °C |
| Average Failure Time | L70(6k) >36000 (h) |

| Materials | |
|-------------------------------|-------------------------|
| Luminaire | steel |
| Reflector | pc |
| Heat sink | extruded aluminum |
| Color available-Bezel | white |
| Color available-Baffle | black/white/piano black |

| Package | |
|------------------|------------------|
| inner box | mm 1 kg |
| outer box | mm 0 kg / 0 in 1 |

Photometric

| Accessories | |
|-------------|--|
| None | |

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.