

IVINA-64H

Product specification



| INTERIOR TRACK LIGHT | |
|-----------------------------|------------------|
| Installation | Track light |
| Cut out | - |
| Dimension | D=Ø64 x H= 205mm |

| Technical description | | | |
|------------------------------|--|--------|--------|
| Article number | 1519.227 | | |
| LED Consumption | 12.8W | | |
| Current | 350mA | | |
| CCT | 2700K | 3000K | 4000K |
| Lumen *1 | 1336lm | 1387lm | 1411lm |
| Øsystem*3 | - | - | - |
| Voltage | 36.5V | | |
| Reflector | 20°/40° | | |
| CRI | 80+ | | |
| Driver | Built in , I/P : 90-264V 50/60HZ O/P : 12-48V 350mA 16w Max | | |

| Technical character | |
|----------------------------|---------------------|
| Insulation | CLASS III |
| Protection | IP 20 |
| Tilt | 0~90° |
| Rotate | 0~355° |
| Operating temperature | -20~40 °C |
| Average Failure Time | L70(10k) >60000 (h) |

| Materials | |
|------------------|----------------------|
| Luminaire | extruded aluminum |
| Reflector | anodized aluminum |
| Heat sink | forged aluminum |
| Gear box | plastic-PC |
| Color available | white / black / grey |

Package

| | |
|-----------|------------------|
| inner box | mm 1 kg |
| outer box | mm 0 kg / 0 in 1 |

Photometric
Accessories

None

Remarks


*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

