URISE

IVINA-120V

Product specification



INTERIOR TRACK LIGHT
Installation Track light
Cut out Dimension D=Ø175 x H= 237mm

Technical description				
•	1440.240			
Article number	1419.210			
LED Consumption	51W			
Current	1400mA			
ССТ	2700K	3000K	4000K	
Lumen *1	5185lm	5393lm	5475lm	
Øsystem ^{*3}	-	-	-	
Voltage	36.4V			
Reflector	20°/40°			
CRI	90+			
Driver	Built in, I/P: 90-264V 50/60HZ			
	O/P: 9-42V 1400mA 60w Max			

Photometric

Technical character		
Insulation	CLASS III	
Protection	IP 20	
Tilt	0~90°	
Rotate	0~355°	
Operating temperature	-20~40 °C	
Average Failure Time	L70(10k) >60000 (h)	

Materials			
Luminaire	extruded aluminum		
Reflector	anodized aluminum		
Heat sink	forged aluminum		
Gear box	aluminum die cast		
Color available	white / black / grey		

Package

inner box - mm 1 kg

outer box - mm 0 kg / 0 in 1

Accessories

None

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX): this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

