


IVINA-100V

Product specification

**INTERIOR TRACK LIGHT**

Installation	Track light
Cut out	-
Dimension	D=Ø100 x H= 155mm

**Technical description**

Article number	1519.201		
LED Consumption	39.1W		
Current	1050mA		
CCT	3000K	3000K	3000K
Lumen ^{*1}	3903lm	4058lm	4121lm
Øsystem ^{*3}	-	-	-
Voltage	37.3V		
Reflector	12°/24°/40°		
CRI	90+		
Driver	Built in , I/P : 90-264V 50/60HZ O/P : 9-48V 1050mA 60w Max		

Technical character

Insulation	CLASS III
Protection	IP 20
Tilt	0~90°
Rotate	0~355°
Operating temperature	-20~40 °C
Average Failure Time	L70(10k) >60000 (h)

Materials

Luminaire	extruded aluminum
Reflector	plastic-PC
Heat sink	forged aluminum
Gear box	aluminum die cast
Color available	white / black / grey

Package

inner box	-	mm	1 kg
outer box	-	mm	0 kg / 0 in 1

Photometric**Accessories**

None

Remarks

*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

