


SLIMDUET-S2



Product specification

INTERIOR SYSTEM LIGHT

Installation	system light
Cut out	-
Dimension	D=Ø64 L=90

**Technical description**

Article number	1617.411-V
LED Consumption	12.7W
Current	-
CCT	3000K
Lumen *1	1114lm
Øsystem*3	-
Voltage	24vdc
Reflector	15°/20°/35°
CRI	90+
Driver	-

Technical character

Insulation	CLASS I
Protection	IP 20
Tilt	90°
Rotate	0~355°
Operating temperature	-20~40 °C
Average Failure Time	L70(10k) >50000 (h)

Materials

Luminaire	extruded aluminum body
Baffle	ABS
Reflector	plastic-PC
Heat sink	extruded aluminum body
Color available-Baffle	white / black / Copper
Color available-Body	white / black

Package

inner box	mm 1 kg
outer box	mm 0 kg / 0 in 1

Photometric**Accessories**

None

Remarks

*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.