


## DEINO



## Product specification

**INTERIOR COMBO LIGHT**

<b>Installation</b>	Ceiling recessed
<b>Cut out</b>	□=170 x 463mm
<b>Dimension</b>	D=□492x191 x H=184mm

**Technical description**

<b>Article number</b>	1614.419		
<b>LED Consumption</b>	25.9W X3		
<b>Current</b>	700mA		
<b>CCT</b>	2700K	3000K	4000K
<b>Lumen <sup>*1</sup></b>	2565lmX3	2670lmX3	2712lmX3
<b>Øsystem<sup>*3</sup></b>	-	-	-
<b>Voltage</b>	37V		
<b>Reflector</b>	18°/26°/38°/55°		
<b>CRI</b>	90+		
<b>Driver</b>	Remoted, I/P : 90-264V 50/60HZ O/P : 15-50V 700mA 35w Max		

**Technical character**

<b>Insulation</b>	CLASS II
<b>Protection</b>	IP 20
<b>Tilt</b>	0~86°
<b>Rotate</b>	0~355°
<b>Operating temperature</b>	-20~40°C
<b>Average Failure Time</b>	L70(10k)>60000(h)

**Materials**

<b>Luminaire</b>	aluminum die cast
<b>Baffle</b>	plastic-PC
<b>Reflector</b>	plastic-PC
<b>Housing</b>	steel
<b>Heat sink</b>	aluminum die cast
<b>Color available:</b>	white / black

**Package**

inner box	-	mm	1 kg
outer box	-	mm	0 kg / 0 in 1

**Photometric****Accessories**

None

**Remarks**

\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

