


## SNOOT



## Product specification

**INTERIOR RECESSED DOWN LIGHT**

<b>Installation</b>	Ceiling recessed
<b>Cut out</b>	<input type="checkbox"/> 99x101
<b>Dimension</b>	D= <input type="checkbox"/> 105 x H= 102mm


**Technical description**

<b>Article number</b>	1614.421		
<b>LED Consumption</b>	13W		
<b>Current</b>	350mA		
<b>CCT</b>	2700K	3000K	4000K
<b>Lumen <sup>*1</sup></b>	1336lm	1387lm	1411lm
<b>Øsystem<sup>*3</sup></b>	-	-	-
<b>Voltage</b>	37.1V		
<b>Reflector</b>	15°/24°/38°/60° 10°(Lens)		
<b>CRI</b>	90+		
<b>Driver</b>	Remoted, I/P : 90-264V 50/60HZ O/P : 12-48V 350mA 16w Max		

**Technical character**

<b>Insulation</b>	CLASS II
<b>Protection</b>	IP44
<b>Tilt</b>	0~20°
<b>Rotate</b>	-
<b>Operating temperature</b>	-20~40°C
<b>Average Failure Time</b>	L70(10k) >60000 (h)

**Materials**

<b>Luminaire</b>	aluminum die cast
<b>Baffle</b>	ABS
<b>Bezel</b>	steel
<b>Reflector</b>	plastic-PC
<b>Heat sink</b>	forged aluminum
<b>Bezel available color</b>	white/black
<b>Baffle available color</b>	white/black

**Photometric**
**Package**

<b>inner box</b>	-	mm 1 kg
<b>outer box</b>	-	mm 0 kg / 0 in 1

**Accessories**

**Remarks**


\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

