




GAGA



## Product specification

**INTERIOR RECESSED DOWN LIGHT**

Installation	Ceiling recessed
Cut out	Ø68
Dimension	D=Ø76 x H= 70mm

**Technical description**

Article number	1618.138		
LED Consumption	13W		
Current	350mA		
CCT	2700K	3000K	4000K
Lumen <sup>*1</sup>	1336lm	1387lm	1411lm
Øsystem <sup>*3</sup>	-	-	-
Voltage	37.1V		
Reflector	15°/24°/38°/60° 10°(Lens)		
CRI	90+		
Driver	Remoted, I/P : 90-264V 50/60HZ O/P : 12-48V 350mA 16w Max		

**Technical character**

Insulation	CLASS II
Protection	IP44
Tilt	0~20°
Rotate	-
Operating temperature	-20~40°C
Average Failure Time	L70(10k) >60000 (h)

**Materials**

Luminaire	aluminum die cast
Reflector	plastic-PC
Heat sink	forged aluminum
Bezel color available	black/white
Baffle color available	black/white/gold

**Package**

inner box	-	mm 1 kg
outer box	-	mm 0 kg / 0 in 1

**Photometric****Accessories****Remarks**

\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

