




GAGA-S



Product specification

INTERIOR RECESSED DOWN LIGHT

Installation	Ceiling recessed
Cut out	Ø68mm
Dimension	D=Ø76 x H= 40mm



Technical description

Article number	1618.100		
LED Consumption	6W		
Current	350mA		
CCT	2700K	3000K	4000K
Lumen ^{*1}	lm	600lm	lm
Øsystem ^{*3}	-	-	-
Voltage	17V		
Reflector	13°/25°/38°		
CRI	90+		
Driver	Remoted, Input 100~240V 50~60Hz Output 350mA 9-24V 8w Max		

Technical character

Insulation	CLASS III
Protection	IP 20
Tilt	0~20°
Rotate	-
Operating temperature	-20~40 °C
Average Failure Time	L70(6k) >36000 (h)

Materials

Luminaire	aluminum die cast
	tempered glass
Reflector	plastic-PC
Heat sink	forged aluminum
Color available	white / black

Package

inner box	mm 1 kg
outer box	mm 0 kg / 0 in 1

Photometric

Accessories

None

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

