




V Buster

-Active circulation

**Product specification****INTERIOR LED PANEL LIGHT**

Installation Ceiling recessed
Dimension L=600 X D=600 X H= 90mm

**Technical description**

Article number	1718.223	
Wattage	55W(PANEL:36W,FAN:19W)	
Lumen ^{*1}		
Øsystem ^{*3}	2800lm	
Voltage	90-264 (VAC)	
beam-angle	110°	
CCT	5000K	
CRI	80+	
Driver	Build-in, I/P : 90-265V 50/60HZ	O/P : 30-40V 900mA Dimmable:Infrared Control

Technical character

Insulation	CLASS I
Protection	IP 20
Operating temperature	-20~40°C
Warranty	3 years
Average Failure Time	L70(6k) >36000 (h)
Signal reception distance	10 meters

Package

inner box 710(L)*710(W)*145(H) mm 8 kg

outer box

Accessories

remote control X 1pc Air enter port filter X 2pcs Air outlet port filter X 6pcs AAA batteryX2pcs

Remarks*1. LUMEN (Typical Pulsed Flux) : for LED chip test result based on $T_j=25^{\circ}\text{C}$, the ambient temperature at 25°C .

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*2. NOMINAL FLUX : this lumen is from LED on heat sink without reflector and fixture.

This loss between LUMEN (Typical Pulsed Flux & NOMINAL FLUX) is the environmental loss.

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture,

this is the real lumen with the loss because of different design of reflectors and fixtures.