



# RHEA-B

RHEA-B, this series has 2 different IP rating to choose from, expand wider application to this series. IP44 is suitable to use in damp location; IP65 has better water resistance, can be used in wet location. RHEA-B are available in fixed and adjustable modules, by using the same trim, this series will make inventory more flexible without pressure. The module and the trim is fixed by clips, making maintenance more convenient.



Color available - A / B






Article number	1718.141
LED Consumption	25.9W
Current	700 (mA)
Lumen	2559 (lm)
Beam Angle	12°/24°/40°
CCT	3000K
CRI	90+

Colours   
Black White



Dimmable





Article number	1718.142
LED Consumption	25.9W
Current	700 (mA)
Lumen	2559 (lm)
Beam Angle	12°/24°/40°
CCT	3000K
CRI	90+

Colours   
Black White



Dimmable






Article number	1618.169
LED Consumption	25.9W
Current	700 (mA)
Lumen	2559 (lm)
Beam Angle	12°/24°/40°
CCT	3000K
CRI	90+

Colours   
Black White



Dimmable



Article number	1618.170
LED Consumption	25.9W
Current	700 (mA)
Lumen	2559 (lm)
Beam Angle	12°/24°/40°
CCT	3000K
CRI	90+

Colours   
Black White



Dimmable

