




HORUS-40W

Product specification**INTERIOR SURFACE MOUNTED CEILING LIGHT**

Installation	Ceiling recessed
Cut out	-
Dimension	D=Ø166 x H= 200mm

**Technical description**

Article number	1213.113		
LED Consumption	39.1W		
Current	1050mA		
CCT	2700K 3000K 4000K		
Lumen ^{*1}	3903lm 4058lm 4121lm		
Øsystem^{*3}	-		
Voltage	37.3V		
Reflector	40°		
CRI	90+		
Driver	Remoted, I/P : 90-264V 50/60HZ O/P : 9-48V 1050mA 60w Max		

Technical character

Insulation	CLASS I
Protection	IP 54
Tilt	-
Rotate	-
Operating temperature	-20~40 °C
Average Failure Time	L70(10k) >60000 (h)

Materials

Luminaire	extruded aluminum
Reflector	anodized aluminum
Heat sink	aluminum die casting
Color available	white / black

Package

inner box	mm 1 kg
outer box	mm 0 kg / 0 in 1

Photometric**Accessories**

None

Remarks

*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.

