



## TEYVAT



## Product specification

## INTERIOR SURFACE MOUNTED WALL LIGHT

Installation Ceiling mounted

Cut out -

Dimension D=Ø111 x H= 131mm



## Technical description

Article number	1813.100		
LED Consumption	25.5W		
Current	700mA		
CCT	2700K	3000K	4000K
Lumen <sup>*1</sup>	2565lm	2670lm	2712lm
Øsystem <sup>*3</sup>	-	-	-
Voltage	36.5V		
Reflector	10°/20°/30°		
CRI	90+		
Driver	Remoted, I/P : 90-264V 50/60HZ O/P : 15-50V 700mA 35w Max		

## Technical character

Insulation	CLASS III
Protection	IP 20
Tilt	-
Rotate	-
Operating temperature	-20~40 °C
Average Failure Time	L70(10k) >60000 (h)

## Materials

Luminaire	aluminum die cast
Reflector	plastic-PC
Heat sink	aluminum die cast
Color available	white / black

## Package

## Photometric

inner box	mm 1 kg
outer box	mm 0 kg / 0 in 1

## Accessories

striped glass , honeycomb louver , Snoot

## Remarks



\*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture,

this is the real lumen with the loss because of different design of reflectors and fixtures.