URISE

MINI GAGA



Product specification

| ESSED DOWN LIGHT | | |
|------------------|--|------------------------|
| ESSED DOWN LIGHT | | |
| Ceiling recessed | ™ • | |
| Ø64mm | | |
| D=Ø95 x H= 64mm | , and the second | |
| | | Ø59 |
| | | Ø95 |
| | | |
| | Ceiling recessed Ø64mm | Ceiling recessed Ø64mm |

| Technical description | | | | |
|-----------------------|----------|-------|-------|--|
| Article number | 1818.239 | | | |
| LED Consumption | 6.4W | | | |
| Current | 350mA | | | |
| сст | 2700K | 3000K | 4000K | |
| Lumen *1 | 504lm | 542lm | 580lm | |
| Øsystem ^{*3} | - | - | - | |
| Voltage | 18.2V | | | |
| Reflector | 50° | | | |
| CRI | 90+ | | | |
| Driver | Remoted | | | |

Photometric

| Technical character | | |
|-----------------------|---------------------|--|
| Insulation | CLASS I | |
| Protection | IP 65 | |
| Tilt | - | |
| Rotate | - | |
| Operating temperature | -20~40 °C | |
| Average Failure Time | L70(10k) >60000 (h) | |

| Materials | | | |
|-----------------|-------------------|--|--|
| Luminaire | aluminum die cast | | |
| Reflector | plastic-PC | | |
| Heat sink | forged aluminum | | |
| Color available | white / black | | |
| | | | |
| | | | |

Package

 inner box
 mm 0 kg

 outer box
 mm 0 kg / 0 in 1

Accessories

None

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

*3. LUMEN(Øsystem) (Total FLUX): this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.