




## WALLED-EYE-S-LED



## Product specification

## INTERIOR RECESSED DOWN LIGHT

<b>Installation</b>	Ceiling recessed
<b>Cut out</b>	Ø123mm
<b>Dimension</b>	D= Ø134 x H= 108mm



## Technical description

<b>Article number</b>	1018.137.0BQR
<b>LED Consumption</b>	15W
<b>Current</b>	350mA
<b>Lumen <sup>*1</sup></b>	1810lm
<b>Øsystem <sup>*3</sup></b>	-
<b>Voltage</b>	39.7V
<b>Reflector</b>	20°/40°
<b>CCT</b>	3000K
<b>CRI</b>	80+
<b>Driver</b>	Remoted, I/P : 90-264V 50/60HZ O/P : 12~48 Vdc/350mA,16Watt max.PF 0.90

## Technical character

<b>Insulation</b>	CLASS III
<b>Protection</b>	IP 20
<b>Tilt</b>	0~30°
<b>Rotate</b>	0~355°
<b>Operating temperature</b>	-20~40 °C
<b>Average Failure Time</b>	L70(6k) >36000 (h)

## Materials

<b>Luminaire</b>	aluminum die cast
<b>Reflector</b>	anodized aluminum
<b>Heat sink</b>	forged aluminum
<b>Color available</b>	white / black

## Package

<b>inner box</b>	mm 1 kg
<b>outer box</b>	mm 0 kg / 0 in 1

## Photometric

## Accessories

## Remarks



\*1. LUMEN (Typical Pulsed Flux) : for LED chip test result based on Tj=25°C", the ambient temperature at 25°C.

This is the ideal (Maximum) lumen. This lumen information is from the LED supplier

\*2. NOMINAL FLUX : this lumen is from LED on heat sink without reflector and fixture.

This loss between LUMEN (Typical Pulsed Flux & NOMINAL FLUX) is the environmental loss.

\*3. LUMEN(Øsystem) (Total FLUX) : this lumen is from luminaire with heat sink, reflector and fixture, this is the real lumen with the loss because of different design of reflectors and fixtures.