





EPIC-135-STLF



Product specification

INTERIOR RECESSED DOWNLIGHTS



Technical Specification

Article number	2018.258A-ACOT-73		
LED Consumption	32W		
Fixture Consumption	36W		
Current / Voltage	900mA / 34.6Vdc		
CRI	90+		
CCT	2700K	3000K	4000K
LED Lumen ^{*1}	3526lm	3667lm	3722lm
Delivered Lumen	-	3170lm	-
Beam Angle available	20°/30°/45°/55°		

Driver Technical Specification (Remoted)


Driver Brand	PHILIPS	Driver Model	929002809106
Input voltage / Frequency range	220-240Vac / 50/60Hz	Output Current / Voltage	900mA / 30-42Vdc
Dimming / Flicker	Non / Low frequency	Certification	ENEC/CCC/CE
Power Factor	>0.9	Warranty	5 years

Technical character


Products Standard	IEC 60598-1	Luminaire	Aluminum die cast
	IEC 62031	Trim	Aluminum die cast
Insulation	CLASS II	Optics	PMMA Lens
Protection	IP44	Heat sink	Forged aluminum
Tilt / Rotate	Non / Non	Fixture color available	white / black
Operating temperature	0~35°C	Baffle	Aluminum die cast
Average Failure Time	L70(9k) >50000(h)	Baffle Color available	white / black

Materials

Accessories

ACSG-1
Striped glassACHO-2
Honeycomb louverACDS-6
Diffusion sheetACWG-1
Woven glassACOT-109
Suction cup

Photometric



Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.