






EPIC-110-RTLW



Product specification

INTERIOR RECESSED DOWNLIGHTS



Cut out :

Technical Specification

Article number	2018.276F-ACOT-84-AM	
LED Consumption	24W (NON-IC)	20W (IC)
Fixture Consumption	30W	25W
Current / Voltage	700mA / 33Vdc	600mA / 33Vdc
CRI	90+	90+
CCT	3000K	3000K
LED Lumen ^{*1}	2987lm	2585lm
Delivered Lumen	1497lm	1184lm
Beam Angle available	30°/40°/50°/60° (Lens)	


Driver Technical Specification (Remoted)

Driver Brand	EUCHIPS	Driver Model	PUP40A-1WMC-850
Input voltage / Frequency range	120-277Vac / 50/60Hz	Output Current / Voltage	700mA / 9-42Vdc
Dimming / Flicker	0/1-10V / Free	Certification	UL
Power Factor	>0.9	Warranty	-

Technical character		Materials	
Products Standard	UL1598	Luminaire	Aluminum die cast
		Trim	Aluminum die cast
Insulation	CLASS III	Optics	PMMA Lens
Protection	Wet Location	Heat sink	Forged aluminum
Tilt / Rotate	None / 0~355°	Fixture color available	white / black
Operating temperature	0~35°C	Baffle	Aluminum die cast
Average Failure Time	L70(10k) >55000(h)	Baffle Color available	white / black

Accessories

Photometric



Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.

INSTALLATION OPTIONS




ACCG-16B-PUP40A-1WMC-850 0/1-10V

ACCG-16B-PUP40D-1WMC-850 DALI

ACCG-16B-PUP40T-1LMC-850 TRIAC

for EPIC110-3.5" (30W)


Type: Gear box



* For single fixture connection only, not available for parallel multiple connection


Internal space dimension:

L 9 13/16" (250mm) X W 2 1/2" (64mm) X H 1 5/16" (34mm)



ACCH-12H-100 for EPIC110-3.5"

Type: New construction plate




ACCH-7B-100-PUP40A-1WMC-850 0/1-10V

ACCH-7B-100-PUP40D-1WMC-850 DALI

ACCH-7B-100-PUP40T-1LMC-850 TRIAC

for EPIC110-3.5" (25W)

Type: IC Box



ACCI-3

Type: Emergency battery holder


For BillDa emergency led driver-

Model NO. BLD-HM08D-YYY

BLD-HM15D-YYY

BLD-HM20D-YYY

BLD-HM25D-YYY



ACCI-5

Type: Remodel stand

