




LENO-85-RTF

Product specification



INTERIOR RECESSED DOWNLIGHTS



75

Technical Specification

| | | | |
|-------------------------|-----------------|--------|--------|
| Article number | 2018.403 | | |
| LED Consumption | 9W | | |
| Fixture Consumption | - | | |
| Current / Voltage | 250mA / 34.4Vdc | | |
| CRI | 90+ | | |
| CCT | 2700K | 3000K | 4000K |
| LED Lumen ^{*1} | 964lm | 1023lm | 1117lm |
| Delivered Lumen | - | - | - |
| Beam Angle available | 15°/24°/38° | | |

Driver Technical Specification (Remoted)

| | | | |
|---------------------------------|----------------------|--------------------------|---|
| Driver Brand | - | Driver Model | - |
| Input voltage / Frequency range | 220-240Vac / 50/60Hz | Output Current / Voltage | - |
| Dimming / Flicker | - | Certification | - |
| Power Factor | - | Warranty | - |

Technical character

| | |
|-----------------------|-------------------|
| Products Standard | IEC 60598-1 |
| | IEC 62031 |
| Insulation | CLASS II |
| Protection | IP20 |
| Tilt / Rotate | None |
| Operating temperature | 0~35°C |
| Average Failure Time | L70(11k)>61000(h) |

Materials

| | |
|-------------------------|-------------------|
| Luminaire | Aluminum die cast |
| Heat sink | Aluminum die cast |
| Fixture color available | white |
| Baffle | Aluminum |
| Baffle Color available | white / black |
| | |
| | |

Accessories

Photometric

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.