





EPIC-135-RTF



Product specification

INTERIOR RECESSED DOWNLIGHTS



Cut out :

Technical Specification

Article number	2018.464-ACOT-73-AM
LED Consumption	36W (NON-IC)
Fixture Consumption	45W
Current / Voltage	1050mA / 34Vdc
CRI	90+
CCT	3000K
LED Lumen ^{*1}	4344lm
Delivered Lumen	3305lm
Beam Angle available	20°/30°/45°/55°

Driver Technical Specification (Remoted)


Driver Brand	EUCHIPS	Driver Model	PUP40A-1WMC-1200
Input voltage / Frequency range	100-240Vac / 50/60Hz	Output Current / Voltage	1050mA / 9-38Vdc
Dimming / Flicker	0/1-10V / Free	Certification	UL
Power Factor	>0.9	Warranty	-

Technical character		Materials	
Products Standard	UL1598	Luminaire	Aluminum die cast
		Trim	Aluminum die cast
Insulation	CLASS II	Optics	PMMA Lens
Protection	Wet Location	Heat sink	Forged aluminum
Tilt / Rotate	Non / Non	Fixture color available	white / black
Operating temperature	0~35°C	Baffle	Aluminum die cast
Average Failure Time	L70(10k)55000(h)	Baffle Color available	white / black

Accessories

ACSG-1
Striped glassACHO-2
Honeycomb louverACDS-6
Diffusion sheetACWG-1
Woven glassACOT-109
Suction cup

Photometric



Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.




ACCG-16B-PUP40A-1WMC-1200 0/1-10V

ACCG-16B-PUP40D-1WMC-1200 DALI

ACCG-16B-PUP40T-1LMC-1200 TRIAC

for EPIC135-4.5"


Type: Gear box



* For single fixture connection only, not available for parallel multiple connection

Internal space dimension:


L $9\frac{13}{16}"$ (250mm) X W $2\frac{1}{2}"$ (64mm) X H $1\frac{5}{16}"$ (34mm)



ACCH-12H-125

for EPIC135-4.5"

Type: New construction plate



ACCI-5

Type: Remodel stand

