






SHELL-S-7-TW



## Product specification

## INTERIOR RECESSED DOWNLIGHTS



## Technical Specification

Article number 2114.418A-AM

LED Consumption 8W

Fixture Consumption 9W

Current / Voltage 180mA / 43.4V

CRI 90+

CCT 3000K

LED Lumen \*1 -

Delivered Lumen 390lm

Beam Angle available Wallwash

## Driver Technical Specification (Remoted)

Driver Brand yg-driver Driver Model LBS12W-48-C0180-RD

Input voltage / Freqency range 100-277Vac / 50/60Hz Output Current / Voltage 180mA / 24-48Vdc

Dimming / Flicker 0-10V Dimming Certification UL / ENEC / CB

Power Factor &gt;0.9 Warranty 5 years


## Technical character

## Materials

Products Standard	UL1598	Luminaire	extruded aluminum
		Trim	extruded aluminum
Insulation	CLASS I	Reflector	PC
Protection	Damp Location	Heat sink	extruded aluminum
Tilt / Rotate	non / non	Fixture color available	white / black
Operating temperature	0~35°C		
Average Failure Time	L70(6k) >36000 (h)		

## Accessories

## Photometric



h(m)	D(m)	E(lx)
Wallwash		
1.0	1.05	283
2.0	2.11	70
3.0	3.17	31
4.0	4.22	17
5.0	5.28	11

## Remarks



\*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.