






SHELL-S-7-TW



Product specification

INTERIOR RECESSED DOWNLIGHTS



Technical Specification

Article number	2114.418A
LED Consumption	8W
Fixture Consumption	10W
Current / Voltage	180mA / 43.4V
CRI	90+
CCT	3000K
LED Lumen *1	-
Delivered Lumen	340lm
Beam Angle available	Wallwash


Driver Technical Specification (Remoted)

Driver Brand	-	Driver Model	-
Input voltage / Freqency range	120-240Vac / 50/60Hz	Output Current / Voltage	180mA / 48Vdc Max.
Dimming / Flicker	-	Certification	-
Power Factor	-	Warranty	-

Technical character		Materials	
Products Standard	IEC 60598-1	Luminaire	extruded aluminum
	IEC 62031	Trim	extruded aluminum
Insulation	CLASS II	Reflector	PC
Protection	IP20	Heat sink	extruded aluminum
Tilt / Rotate	non / non	Fixture color available	white / black
Operating temperature	0~35°C		
Average Failure Time	L70(6k) >36000 (h)		

Accessories

Photometric



h (m)	D (m)	E (lx)
Wallwash		
1.0	1.05	283
2.0	2.11	70
3.0	3.17	31
4.0	4.22	17
5.0	5.28	11

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.