



SHELL-S-14-TW



## Product specification

## INTERIOR RECESSED DOWNLIGHTS



## Technical Specification

Article number	2114.418B
LED Consumption	15W
Fixture Consumption	17W
Current / Voltage	350mA / 43.4V
CRI	90+
CCT	3000K
LED Lumen <sup>*1</sup>	-
Delivered Lumen	757lm
Beam Angle available	Wallwash


## Driver Technical Specification (Remoted)

Driver Brand	-	Driver Model	-
Input voltage / Freqency range	120-240Vac / 50/60Hz	Output Current / Voltage	350mA / 48Vdc Max.
Dimming / Flicker		Certification	-
Power Factor	-	Warranty	-

Technical character		Materials	
Products Standard	IEC 60598-1	Luminaire	extruded aluminum
	IEC 62031	Trim	extruded aluminum
Insulation	CLASS II	Reflector	PC
Protection	IP20	Heat sink	extruded aluminum
Tilt / Rotate	non / non	Fixture color available	white / black
Operating temperature	0~35°C		
Average Failure Time	L70(6k) >36000 (h)		

## Accessories

## Photometric



h(m)	D(m)	E(lx)
Wallwash		
1.0	1.01	588
2.0	2.03	147
3.0	3.04	65
4.0	4.05	36
5.0	5.06	23

## Remarks



\*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.