




TEQUILA-110-RSFP-1



Product specification

INTERIOR PENDANT LIGHTS



Technical Specification

Article number	2116.119C		
LED Consumption	26W		
Fixture Consumption	30W		
Current / Voltage	700mA / 36.5Vdc		
CRI	90+		
CCT	2700K	3000K	4000K
LED Lumen ^{*1}	2565lm	2670lm	2712lm
Delivered Lumen	-	1890lm	-
Beam Angle available	15°/24°/38° (Reflector)		

Driver Technical Specification (Built-in)

Driver Brand	HEP	Driver Model	LNC30W700LRP
Input voltage / Frequency range	220-240Vac / 50/60Hz	Output Current / Voltage	700mA / 25-42Vdc
Dimming / Flicker	Non / Free	Certification	ENEC / CE
Power Factor	>0.9	Warranty	5 years

Technical character

Products Standard	IEC 60598-1
	IEC 62031
Insulation	CLASS II
Protection	IP20
Tilt / Rotate	non / non
Operating temperature	0~35°C
Average Failure Time	L70(10k) >60000(h)


Materials

Luminaire	extruded aluminum
Trim	-
Reflector	PC
Heat sink	extruded aluminum
Fixture color available	white / black
Magnetic baffle	PC
Baffle Color available	white / black / chrome / matt gold


Accessories

ACCL-1
Clear glassACSG-2
Striped glassACDS-1
Diffusion sheetACHO-3
Honeycomb louver


Photometric



h(m)	D(m)	E(lx)
24°		
1.0	0.40	10223
2.0	0.79	2556
3.0	1.19	1136
4.0	1.59	638
5.0	1.98	408



h(m)	D(m)	E(lx)
30°		
1.0	0.54	6405
2.0	1.09	1601
3.0	1.63	711
4.0	2.18	400
5.0	2.72	256



h(m)	D(m)	E(lx)
35°		
1.0	0.62	4072
2.0	1.24	1018
3.0	1.85	452
4.0	2.47	254
5.0	3.09	162

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.