




TEQUILA-64-RSFP-3



Product specification

INTERIOR PENDANT LIGHTS



Technical Specification

Article number	2116.122A		
LED Consumption	13W		
Fixture Consumption	16W		
Current / Voltage	350mA / 36.5Vdc		
CRI	90+		
CCT	2700K	3000K	4000K
LED Lumen ^{*1}	1336lm	1387lm	1411lm
Delivered Lumen	-	1055lm	-
Beam Angle available	15°/24°/38°		

Driver Technical Specification (Built-in)

Driver Brand	HEP	Driver Model	LSC20W350LRP UNI
Input voltage / Frequency range	100-277Vac / 50/60Hz	Output Current / Voltage	350mA / 32-55Vdc
Dimming / Flicker	Non / Free	Certification	ENEC / CE
Power Factor	>0.9	Warranty	5 years


Technical character

Products Standard	IEC 60598-1	Luminaire	extruded aluminum
	IEC 62031	Trim	-
Insulation	CLASS II	Reflector	PC
Protection	IP20	Heat sink	extruded aluminum
Tilt / Rotate	non / non	Fixture color available	white / black
Operating temperature	0~35°C	Magnetic baffle	PC
Average Failure Time	L70(10k) >60000(h)	Baffle Color available	white / black / chrome / matt gold


Accessories

ACCL-2
Clear glassACSG-3
Striped glassACDS-2
Diffusion sheetACHO-4
Honeycomb louver


Photometric



h (m)	D (m)	E (lx)
24°		
1.0	0.46	4334
2.0	0.92	1083
3.0	1.37	481
4.0	1.83	270
5.0	2.29	173



h (m)	D (m)	E (lx)
36°		
1.0	0.59	3032
2.0	1.18	758
3.0	1.77	336
4.0	2.36	189
5.0	2.95	121



h (m)	D (m)	E (lx)
45°		
1.0	0.79	1825
2.0	1.58	456
3.0	2.36	202
4.0	3.15	114
5.0	3.94	72

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.