




BROWNIE 40-S2-2



Product specification

SYSTEM LIGHTS



Technical Specification

Article number 2117.409-V-AM

LED Consumption 30W

Fixture Consumption

Current / Voltage 700mA /36Vdc

CRI 90+

CCT 3000K

LED Lumen *1 2376lm

Delivered Lumen

Beam Angle available 20°/30°/40°

Driver Technical Specification (Remoted)

Driver Brand	ERP	Driver Model	PSB30W-0700-42
Input voltage / Freqency range	120-277Vac / 50/60Hz	Output Current / Voltage	700mA / 27-42Vdc
Dimming / Flicker	0/1~10V/Free	Certification	UL/CE
Power Factor	>0.9	Warranty	5years

Technical character

Materials

Products Standard	UL 1598	Luminaire	extruded aluminum
	CSA C22.2#250.0	Trim	-
Insulation	CLASS II	Optics	PC
Protection	IP20	Heat sink	extruded aluminum
Tilt / Rotate	0~90° / 0~355°	Fixture color available	white / black
Operating temperature	0~35°C	Baffle	
Average Failure Time	L70(6k) >36000 (h)	Baffle Color available	white / black / copper

Accessories

Photometric

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.