




## BROWNIE 40-C1



## Product specification

## SYSTEM LIGHTS



| Technical Specification                              |                    |                          |                        |
|------------------------------------------------------|--------------------|--------------------------|------------------------|
| Article number                                       |                    | 2117.412-V               |                        |
| LED Consumption                                      |                    | 6.4W                     |                        |
| Fixture Consumption                                  |                    |                          |                        |
| Current / Voltage                                    |                    | 350mA /18Vdc             |                        |
| CRI                                                  |                    | 90+                      |                        |
| CCT                                                  |                    | 3000K                    |                        |
| LED Lumen <sup>*1</sup>                              |                    | 557lm                    |                        |
| Delivered Lumen                                      |                    |                          |                        |
| Beam Angle available                                 |                    | 20°/25°/35°              |                        |
| Driver Technical Specification (Remoted)             |                    |                          |                        |
| Driver Brand YG                                      |                    | Driver Model             | LBS12W-36-C0350-RD     |
| Input voltage / Frequency range 120-277Vac / 50/60Hz |                    | Output Current / Voltage | 350mA / 18-36Vdc       |
| Dimming / Flicker 0/1~10V/Free                       |                    | Certification            | UL/CE                  |
| Power Factor >0.9                                    |                    | Warranty                 | 5years                 |
| Technical character                                  |                    | Materials                |                        |
| Products Standard                                    | IEC 60598-1        | Luminaire                | extruded aluminum      |
|                                                      | IEC 62031          | Trim                     | -                      |
| Insulation                                           | CLASS II           | Optics                   | PC                     |
| Protection                                           | IP20               | Heat sink                | extruded aluminum      |
| Tilt / Rotate                                        |                    | Fixture color available  | white / black          |
| Operating temperature                                | 0~35°C             | Baffle                   |                        |
| Average Failure Time                                 | L70(6k) >36000 (h) | Baffle Color available   | white / black / copper |

## Accessories

## Photometric

## Remarks



\*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.