





## BROWNIE 40-C3



## Product specification

## SYSTEM LIGHTS



## Technical Specification

|                                          |                      |
|------------------------------------------|----------------------|
| Article number                           | 2117.414-V           |
| LED Consumption                          | 6.4W                 |
| Fixture Consumption                      |                      |
| Current / Voltage                        | 350mA /18Vdc         |
| CRI                                      | 90+                  |
| CCT                                      | 3000K                |
| LED Lumen <sup>*1</sup>                  | 557lm                |
| Delivered Lumen                          |                      |
| Beam Angle available                     | 20°/25°/35°          |
| Driver Technical Specification (Remoted) |                      |
| Driver Brand                             | YG                   |
| Driver Model                             | LBS12W-36-C0350-RD   |
| Input voltage / Frequency range          | 120-277Vac / 50/60Hz |
| Output Current / Voltage                 | 350mA / 18-36Vdc     |
| Dimming / Flicker                        | 0/1~10V/Free         |
| Certification                            | UL/CE                |
| Power Factor                             | >0.9                 |
| Warranty                                 | 5years               |

| Technical character   |                    | Materials               |                        |
|-----------------------|--------------------|-------------------------|------------------------|
| Products Standard     | IEC 60598-1        | Luminaire               | extruded aluminum      |
|                       | IEC 62031          | Trim                    | -                      |
| Insulation            | CLASS II           | Optics                  | PC                     |
| Protection            | IP20               | Heat sink               | extruded aluminum      |
| Tilt / Rotate         |                    | Fixture color available | white / black          |
| Operating temperature | 0~35°C             | Baffle                  |                        |
| Average Failure Time  | L70(6k) >36000 (h) | Baffle Color available  | white / black / copper |

## Accessories

## Photometric

## Remarks



\*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.