




## BROWNIE 60-C4



## Product specification

## SYSTEM LIGHTS



## Technical Specification

|                                          |                      |                          |                    |
|------------------------------------------|----------------------|--------------------------|--------------------|
| Article number                           | 2117.423-V           |                          |                    |
| LED Consumption                          | 13W                  |                          |                    |
| Fixture Consumption                      |                      |                          |                    |
| Current / Voltage                        | 350mA /36Vdc         |                          |                    |
| CRI                                      | 90+                  |                          |                    |
| CCT                                      | 3000K                |                          |                    |
| LED Lumen *1                             | 951lm                |                          |                    |
| Delivered Lumen                          |                      |                          |                    |
| Beam Angle available                     | 20°/25°/35°          |                          |                    |
| Driver Technical Specification (Remoted) |                      |                          |                    |
| Driver Brand                             | YG                   | Driver Model             | LBS20W-48-C0350-RD |
| Input voltage / Frequency range          | 120-277Vac / 50/60Hz | Output Current / Voltage | 350mA / 24-48Vdc   |
| Dimming / Flicker                        | 0/1~10V/Free         | Certification            | UL/CE              |
| Power Factor                             | >0.9                 | Warranty                 | 5years             |

| Technical character   |                    | Materials               |                        |
|-----------------------|--------------------|-------------------------|------------------------|
| Products Standard     | IEC 60598-1        | Luminaire               | extruded aluminum      |
|                       | IEC 62031          | Trim                    | -                      |
| Insulation            | CLASS II           | Optics                  | PC                     |
| Protection            | IP20               | Heat sink               | extruded aluminum      |
| Tilt / Rotate         |                    | Fixture color available | white / black          |
| Operating temperature | 0~35°C             | Baffle                  |                        |
| Average Failure Time  | L70(6k) >36000 (h) | Baffle Color available  | white / black / copper |

## Accessories

## Photometric

## Remarks



\*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.