




BROWNIE 60-C2



## Product specification

## SYSTEM LIGHTS



## Technical Specification

Article number 2117.425-V-AM

LED Consumption 15W

Fixture Consumption

Current / Voltage 350mA /36Vdc

CRI 90+

CCT 3000K

LED Lumen \*1 951lm

Delivered Lumen

Beam Angle available 20°/25°/35°

## Driver Technical Specification (Remoted)

Driver Brand EUCHIPS Driver Model PUP20A-1WMC

Input voltage / Freqency range 120-277Vac / 50/60Hz Output Current / Voltage 350mA / 9-45Vdc

Dimming / Flicker 0/1~10V/Free Certification UL/CE

Power Factor &gt;0.9 Warranty 5years

## Technical character

## Materials

Products Standard UL 1598 Luminaire extruded aluminum

CSA C22.2#250.0 Trim -

Insulation CLASS II Optics PC

Protection IP20 Heat sink extruded aluminum

Tilt / Rotate Fixture color available white / black

Operating temperature 0~35°C Baffle

Average Failure Time L70(6k) &gt;36000 (h) Baffle Color available white / black / copper

## Accessories

## Photometric

## Remarks



\*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.