





EPIC-85-STW



Product specification

INTERIOR RECESSED DOWNLIGHTS



Technical Specification

Article number	2118.111-ACOT-70		
LED Consumption	12W		
Fixture Consumption	15W		
Current / Voltage	350mA / 33.8Vdc		
CRI	90+		
CCT	2700K	3000K	4000K
LED Lumen ^{*1}	1389lm	1446lm	1469lm
Delivered Lumen	-	627lm	-
Beam Angle available	Wallwash		


Driver Technical Specification (Remoted)

Driver Brand	-	Driver Model	-
Input voltage / Frequency range	-	Output Current / Voltage	-
Dimming / Flicker	-	Certification	-
Power Factor	-	Warranty	-

Technical character		Materials	
Products Standard	IEC 60598-1	Luminaire	Aluminum die cast
	IEC 62031	Trim	Aluminum die cast
Insulation	CLASS II	Optics	PMMA Lens
Protection	IP44	Heat sink	Forged aluminum
Tilt / Rotate	Non / Non	Fixture color available	white / black
Operating temperature	0~35°C	Baffle	Aluminum die cast
Average Failure Time	L70(9k)>50000(h)	Baffle Color available	white / black

Accessories

Photometric



h (m)	D (m)	E (lx)
Wallwash		
1.0	0.63	995
2.0	1.26	248
3.0	1.89	110
4.0	2.52	62
5.0	3.15	39

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.