




STELLAR-110-RTA



Product specification

INTERIOR RECESSED DOWNLIGHTS



100

Technical Specification

Article number	2118.192-ACOT-72		
LED Consumption	25W		
Fixture Consumption	28W		
Current / Voltage	700mA / 35.5Vdc		
CRI	90+		
CCT	2700K	3000K	4000K
LED Lumen ^{*1}	2763lm	2873lm	2918lm
Delivered Lumen	-	2394lm	-
Beam Angle available	30°/40°/50°/55° (Lens)		

Driver Technical Specification (Remoted)

Driver Brand	-	Driver Model	-
Input voltage / Frequency range	-	Output Current / Voltage	-
Dimming / Flicker	-	Certification	-
Power Factor	-	Warranty	-


Technical character

Products Standard	IEC 60598-1
	IEC 62031
Insulation	CLASS II
Protection	IP44
Tilt / Rotate	0~30° / 0~355°
Operating temperature	0~35°C
Average Failure Time	L70(12k)>64000(h)

Materials

Luminaire	Aluminum die cast
Trim	Aluminum die cast
Optics	PMMA Lens
Heat sink	Forged aluminum
Fixture color available	white / black
Baffle	Aluminum die cast
Baffle Color available	white / black

Accessories

SG7-1
Striped glassH7-1
Honeycomb louverDS7-1
Diffusion sheetWG7-1
Woven glass

h(m)	D(m)	E(lx)
40°		
1.0	0.74	5089
2.0	1.48	1272
3.0	2.22	565
4.0	2.96	318
5.0	3.70	203

ACOT-82
MR16 Accessory kitsACOT-83
GU10 Accessory kitsPJ-0079
MR16&GU10 Accessory

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.