


INTERIOR RECESSED DOWNLIGHTS


60

Technical Specification


Article number	2118.200F-ACOT-69-WCW		
LED Consumption	10W		
Fixture Consumption	11W		
Current / Voltage	250mA / 36Vdc		
CRI	90+		
CCT	2700K	3000K	4000K
LED Lumen ^{*1}	872lm	913lm	981lm
Delivered Lumen	-	766lm	-
Beam Angle available	20°/40°/55°		

Driver Technical Specification (Remoted)

Driver Brand	-	Driver Model	-
Input voltage / Frequency range	-	Output Current / Voltage	-
Dimming / Flicker	-	Certification	-
Power Factor	-	Warranty	-

Technical character

Products Standard	IEC 60598-1	Luminaire	Aluminum die cast
	IEC 62031	Trim	Aluminum die cast
Insulation	CLASS II	Optics	PMMA Lens
Protection	IP44	Heat sink	Forged aluminum
Tilt / Rotate	Non / Non	Fixture color available	white / black
Operating temperature	0~35°C	Baffle	Aluminum die cast
Average Failure Time	L70(6k) >33300(h)	Baffle Color available	white / black



Accessories
Photometric
ACSG-5
Striped glassACHO-6
Honeycomb louverACDS-3
Diffusion sheetACWG-6
Woven glassACOT-107
Suction cup
Remarks


*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.

20°

Fixed UGR<13

2118.100-ACOT-68
2118.200F-ACOT-68





H(m)	D(m)	E(lx)
20°		
1.0	0.36	4633
2.0	0.72	1158
3.0	1.08	514
4.0	1.44	299
5.0	1.80	185

40°

Fixed UGR<16

2118.100-ACOT-68
2118.200F-ACOT-68





H(m)	D(m)	E(lx)
40°		
1.0	0.77	1485
2.0	1.55	366
3.0	2.32	162
4.0	3.10	91
5.0	3.87	58

55°

Fixed UGR<22

2118.100-ACOT-68
2118.200F-ACOT-68



H(m)	D(m)	E(lx)
55°		
1.0	0.94	1022
2.0	1.89	255
3.0	2.83	113
4.0	3.78	63
5.0	4.72	40