





EPIC-65-RTLA



Product specification

INTERIOR RECESSED DOWNLIGHTS



60

Technical Specification

Article number 2118.201F-ACOT-68

LED Consumption 10W

Fixture Consumption 11W

Current / Voltage 250mA / 36.5Vdc

CRI 90+

CCT 2700K 3000K 4000K

LED Lumen ¹ 872lm 913lm 981lm

Delivered Lumen - 767lm -

Beam Angle available 20°/40°/55°

Driver Technical Specification (Remoted)


Driver Brand	-	Driver Model	-
Input voltage / Freqency range	-	Output Current / Voltage	-
Dimming / Flicker	-	Certification	-
Power Factor	-	Warranty	-

Technical character


Materials

Products Standard	IEC 60598-1	Luminaire	Aluminum die cast
	IEC 62031	Trim	Aluminum die cast
Insulation	CLASS II	Optics	PMMA Lens
Protection	IP44	Heat sink	Forged aluminum
Tilt / Rotate	0~30° / Non	Fixture color available	white / black
Operating temperature	0~35°C	Baffle	Aluminum die cast
Average Failure Time	L70(6k) >33300(h)	Baffle Color available	white / black


Accessories

ACSG-5
Striped glassACHO-6
Honeycomb louverACDS-3
Diffusion sheetACWG-6
Woven glassACOT-107
Suction cup


Photometric



h (m)	D (m)	E (lx)
20°		
1.0	0.35	4878
2.0	0.69	1220
3.0	1.04	542
4.0	1.38	305
5.0	1.73	195



h (m)	D (m)	E (lx)
40°		
1.0	0.75	1540
2.0	1.50	384
3.0	2.26	171
4.0	3.01	96
5.0	3.76	61



h (m)	D (m)	E (lx)
55°		
1.0	0.94	1017
2.0	1.89	254
3.0	2.83	113
4.0	3.78	63
5.0	4.73	40

Remarks

*1. LUMEN : for LED chip test result based on $T_c=85^{\circ}\text{C}$. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.