




BRAVO-85-RTF2



Product specification

INTERIOR RECESSED DOWNLIGHTS



80

Technical Specification

Article number	2118.555-ACOT-88
LED Consumption	10W
Fixture Consumption	-
Current / Voltage	800mA / 12Vdc
CRI	90+
CCT	3000K
LED Lumen *1	774lm
Delivered Lumen	380lm
Beam Angle available	9° (Lens)


Driver Technical Specification (Remoted)

Driver Brand	-	Driver Model	-
Input voltage / Freqency range	-	Output Current / Voltage	-
Dimming / Flicker	-	Certification	-
Power Factor	-	Warranty	-

Technical character		Materials	
Products Standard	IEC 60598-1	Luminaire	Aluminum die cast
	IEC 62031	Trim	Aluminum die cast
Insulation	CLASS II	Optics	PC Lens
Protection	IP44	Heat sink	Forged aluminum
Tilt / Rotate	Non / Non	Fixture color available	white / black
Operating temperature	0~35°C	Baffle	Aluminum die cast
Average Failure Time	L80(12k)>72600(h)	Baffle Color available	white / black

Accessories

Photometric



h(m)	D(m)	E(lx)
9°		
1.0	0.16	9365
2.0	0.33	2341
3.0	0.49	1041
4.0	0.65	585
5.0	0.82	374

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.