





BRAVO-85-STA2



Product specification

INTERIOR RECESSED DOWNLIGHTS



Technical Specification

Article number	2118.562-ACOT-36		
LED Consumption	14W		
Fixture Consumption	-		
Current / Voltage	350mA / 38.4Vdc		
CRI	90+		
CCT	2700K	3000K	4000K
LED Lumen ^{*1}	1139lm	1193lm	1282lm
Delivered Lumen	-	969lm	-
Beam Angle available	15°/24°/50° (Lens)		

Driver Technical Specification (Remoted)

Driver Brand	-	Driver Model	-
Input voltage / Frequency range	-	Output Current / Voltage	-
Dimming / Flicker	-	Certification	-
Power Factor	-	Warranty	-


Technical character

Products Standard	IEC 60598-1	Luminaire	Aluminum die cast
	IEC 62031	Trim	Aluminum die cast
Insulation	CLASS II	Optics	PMMA Lens
Protection	IP44	Heat sink	Forged aluminum
Tilt / Rotate	0~30° / Non	Fixture color available	white / black
Operating temperature	0~35°C	Baffle	Aluminum die cast
Average Failure Time	-	Baffle Color available	white / black


Accessories

SG7-1
Striped glassH7-1
Honeycomb louverDS7-1
Diffusion sheetWG7-1
Woven glassACOT-82
MR16 Accessory kitsACOT-83
GU10 Accessory kitsPJ-0079
MR16&GU10 Accessory


Photometric




h(m)	D(m)	E(lx)
15°		
1.0	0.23	11202
2.0	0.46	2801
3.0	0.69	1245
4.0	0.92	700
5.0	1.15	448



h(m)	D(m)	E(lx)
24°		
1.0	0.46	4903
2.0	0.91	1226
3.0	1.37	544
4.0	1.82	306
5.0	2.28	196



h(m)	D(m)	E(lx)
36°		
1.0	0.65	2720
2.0	1.30	680
3.0	1.95	302
4.0	2.60	170
5.0	3.26	108



h(m)	D(m)	E(lx)
50°		
1.0	0.87	1585
2.0	1.73	396
3.0	2.60	176
4.0	3.46	99
5.0	4.33	63

Remarks



*1. LUMEN : for LED chip test result based on Tc=85°C. This is the ideal (Maximum) lumen. This lumen information is from the LED supplier.